## LEGEND METAL SEATING CONSTRUCTION -

- Fully welded chair frame is constructed of 14 gauge 11/2 x 1/2", 11/2 x 3/4" and 1 x 1" steel tubing, and 1/8" and 3/16" thick formed steel components and powder coated for long life
- Contoured back panel is constructed of laminated, high density hardwood veneers using a RF process and a UF resin with very low off gas emissions
- Plywood seat panel is covered with a hytrel elastomer composite that retains its original shape
- Foam contains environmentally-friendly bio-based materials, and is California TB117-2013 Compliant

## FEATURES -

- Fully welded design ensures long-term structural integrity
- $\cdot\,$  All fasteners are tamper-resistant
- $\cdot\,$  Wallsaver leg design protects walls from damage
- · Nylon glides are non-removable and protect floors from damage

## OPTIONS -

- $\cdot\,$  Custom frame and arm cap finishes
- Choice of wood, polyurethane or solid surface arm caps
- Contrasting fabrics
- Bolt-to-floor brackets

## Added weight

· Moisture barrier





arms

24.5

25.25

34.25

18

21

1

2

26.5

0.75

50 lbs

500 lbs





arms

27.5

25.25

34.25

18

24

1

26.5

0.75

54 lbs

500 lbs

2



Guest Chair

34.5

25.25

34.25

18

31

26.5

1.75

1.25

65 lbs

750 lbs

1



LHD-21			
Guest Chair			

24.5

25.25

34.25

18

21

1

1

26.5

0.75

50 lbs

500 lbs

LH

LHD-21-CAF Guest Chair, fully closed

**LHD-24** Guest Chair

27.5

25.25

34.25

18

24

1

1

26.5

0.75

54 lbs

500 lbs


LHD-24-CAF Guest Chair, fully closed





LHD-31-CAF	
Guest Chair, fu	
arms	
34.5	





	LTF-1818-16-BH Free Standing Table	LTF-1842-16-BH Free Standing Table
Width	18	18
Depth	18	42
Height	16	16
Weight	24 lbs	42 lbs

T +1 877 395 2623

F +1 877 395 6270

45 Goodrich Drive, Kitchener ON, N2C 0B8

Width

Depth

Height Seat Height

Seat Width

Arm Height

Ship Weight

Weight Rating\*

COM Yard Back

COM Yard Seat

COM Yard Arms

E sales@stancehealthcare.com stancehealthcare.com



\* Certified to BIFMA X5.4–2012 Standard. Weights listed are extrapolated from the Seating Durability and DropText procedures of this standard.

