KITE METAL SEATING CONSTRUCTION -	FEATURES -	OPTIONS -	
<ul> <li>Frame constructed of 14 and 16-gauge powdercoated steel</li> </ul>	• Metal frame constructed of 14 and 16-gauge material	Custom finishes	
$\cdot$ Contoured seat and back panels are constructed of laminated, high density	<ul> <li>Contoured back and waterfall seat design provide a comfortable sit</li> </ul>	Contrasting fabrics	
hardwood veneers using a RF process and a UF resin with very low off-gas emissions		Protective wall bumper on chair back	
<ul> <li>Foam contains environmentally-friendly bio-based materials, and is California TB117-2013 compliant</li> </ul>	• Chair depth when mounted to wall is 7.5"	Moisture barrier	
	$\cdot$ Available in 16" and 18" seat widths		
	<ul> <li>Available heavy duty steel bracket for secure wall mounting</li> </ul>		
	· Exceeds ANSI/BIFMA X5.4-2020		







			-	
	<b>KT400</b> 16″ Metal Folding Chair	<b>KT500</b> 18″ Metal Folding Chair	<b>KICWB</b> Wall-mount Bracket	
Width	19	21	7.5	
Depth	22	22	2.5	
Height	34	34	6	
Seat Width	16	18	_	
Seat Depth	16.5	16.5	_	
Seat Height	18	18	-	
COM Yard Back	0.5	0.5	_	
COM Yard Seat	0.5	0.5	_	
Ship Weight	19 lbs	20 lbs	-	
Weight Rating*	400 lbs	400 lbs	-	

45 Goodrich Drive, Kitchener ON, N2C 0B8

ve, T +1 877 395 2623 2C 0B8 F +1 877 395 6270 E sales@stancehealthcare.com stancehealthcare.com



\* Certified to BIFMA X5.4–2012 Standard. Weights listed are extrapolated from the Seating Durability and Drop Test procedures of this standard.

