## OASIS METAL SEATING CONSTRUCTION -

- Back constructed of a welded armature consisting of 14-gauge tubing and 3/16" flat bar, and is molded into the foam
- Fully-welded side frames are constructed of powdercoated 14-gauge, 15/8" round steel tubing and 3/16" thick stretchers
- $\cdot$  Fully-welded seat frame is constructed of powdercoated 11-gauge, 1 x 1/2" and 1 x 2" steel tubing, and 1/8" and 3/16" thick formed steel components
- Plywood seat panel is covered with a hytrel elastomer composite that retains its original shape for long life and enhanced comfort
- Foam contains environmentally-friendly bio-based materials, and is California TB117-2013 compliant

- · 14-gauge powder coated steel frame
- · Available in 21" and 31" seat widths
- Upholstery covers and arm caps are easily replaced if necessary
- Arm caps designed for easy ingress and egress
- · Clean-out spacing between seat and back

OPTIONS -

- $\cdot \,$  Choice of wood, polyurethane or solid surface arm caps
- Contrasting fabrics
- Custom finishes
- · Moisture barrier



	<b>SO6501</b> Single Chair	<b>SO6508</b> 31" Chair
Width	25.5	35.5
Depth	25.5	25.5
Height	34.5	34.5
Seat Width	21	31
Seat Height	18.5	18.5
Arm Height	26	26
COM Yard Back	1.25	1.75
COM Yard Seat	0.75	1.25
Ship Weight	50 lbs	78 lbs
Weight Rating*	500 lbs	750 lbs

45 Goodrich Drive, Kitchener ON, N2C 0B8 T +1 877 395 2623 E sales F +1 877 395 6270 **stance** 





