

OASIS METAL SEATING CONSTRUCTION –

- Back constructed of a welded armature consisting of 14-gauge tubing and 3/16" flat bar, and is molded into the foam
- Fully-welded side frames are constructed of powdercoated 14-gauge, 1 5/8" round steel tubing and 3/16" thick stretchers
- Fully-welded seat frame is constructed of powdercoated 11-gauge, 1 x 1/2" and 1 x 2" steel tubing, and 1/8" and 3/16" thick formed steel components
- Plywood seat panel is covered with a hytel elastomer composite that retains its original shape for long life and enhanced comfort
- Foam contains environmentally-friendly bio-based materials, and is California TB117-2013 compliant

FEATURES –

- 14-gauge powder coated steel frame
- Available in 21" and 31" seat widths
- Upholstery covers and arm caps are easily replaced if necessary
- Arm caps designed for easy ingress and egress
- Clean-out spacing between seat and back

OPTIONS –

- Choice of wood, polyurethane or solid surface arm caps
- Contrasting fabrics
- Custom finishes
- Moisture barrier



SO6501
Single Chair



SO6508
31" Chair



UCT-90R
Radius Corner Table



CT-28C-M
Square Corner Table



UCT-SP
Square Spacer Table

Width	25.5	35.5	28	28	22
Depth	25.5	25.5	28	28	22
Height	34.5	34.5	17	17	17
Seat Width	21	31	–	–	–
Seat Height	18.5	18.5	–	–	–
Arm Height	26	26	–	–	–
COM Yard Back	1.25	1.75	–	–	–
COM Yard Seat	0.75	1.25	–	–	–
Ship Weight	50 lbs	78 lbs	–	–	–
Weight Rating*	500 lbs	750 lbs	–	–	–

