

Stance



602 MYSTIC WHITE



63 VANILLA



605 CREAM



609 TAUPE



802 MOCHA




809 CHOCOLATE




306 NAVAL BLUE




303 DENIM BLUE




91 DOVE



902 SEAGULL



905 STEEL



97 SLATE




83 TAN




804 AMBER




88 TOBACCO



98 CHARCOAL



908 CHINCHILLA



909 RAVEN



17 GARNET



102 CHAMPAGNE

CHALLENGER



EASY CLEANABILITY

Endurepel Armour is our performance finish applied to Challenger providing tough anti-stain, anti-bacterial, anti-mildew and anti-pinking properties. This finish ensures mild soap and water will conveniently clean most stains.

ECO-FRIENDLY

Challenger is a performance vinyl with the added benefit of being environmentally-friendly. Challenger is Prop 65 compliant, FR additive free, REACH compliant, phthalate free, formaldehyde free, heavy metal and lead-free. Over 99% of solvents recaptured and recycled.

CARE INSTRUCTIONS

STAIN	MILD DETERGENT
Food condiments & oils	✓
Red Wine, Liquor	✓
Coffee, Tea, Soda, Milk	✓
Cosmetics	✓
Urine, Blood	✓
Chocolate	✓

- » Prompt cleaning recommended.
- » Clean most stains with mild soap and water, then rinse with fresh water to remove residue and wipe dry with a clean cloth.
- » Lift most tough stains with alcohol-based or peroxide-based cleaners.
- » Cleanable with Virox 5, Oxivir Plus, Oxivir TB, Oxivir TB wipes, Accel Five TB, Accel PREvention, Accel PREvention wipes, Oasis 146 and bleach. Dilution ratios must be followed. Rinse the cleaned area after with fresh water and wipe dry with a clean cloth.

GRADE 1

SPECIFICATIONS

ABRASION	Exceeds 1,500,000 Double Rubs
ANTI-PINKING	Passes ASTM 1428
CONTENT	100% Polyvinyl Chloride (PVC)
BACKING CONTENT	100% Polyester
CLEANING CODE	W - Clean fabrics with water-based cleaning agents or water based foam
COLD CRACK	-55°C [-67°F]
COLORS	20 available
CROCKING	AATCC 8: Dry = Class 5, Wet = Class 5
ELONGATION	Passes ASTM D751: Weft 116%, Warp 64%
FIRE RETARDANCY*	CALTB117-2013, IMO FTP Code 2010 - Part 8, MVSS302, NFPA 260 Class 1, UFAC Class 1
ANTI-BACTERIAL	Passes AATCC 147-2011
MILDEW RESISTANT	Passes ASTM G21-13
PROTECTIVE FINISH	Endurepel Armour
SEAM SLIPPAGE	Passes ASTM D751: Weft = 64 lbs., Warp = 67 lbs.
TEAR STRENGTH	Passes ASTM D2261: Weft = 13 lbs., Warp = 10 lbs, Passes ASTM D751: Weft = 12 lbs., Warp = 10 lbs
TENSILE STRENGTH	Passes ASTM D751: Weft = 94 lbs., Warp = 101 lbs
THICKNESS	1.10 mm
UV/LIGHTFASTNESS	AATCC 16.3 - Grade 4.0 (1,500 hours)
WEIGHT	21.71 oz./yd ² 33.17 oz./lin. yd
WIDTH	55" (140 cm)
ROLL SIZE	30 yd; 27 m

Challenger is protected with a 3 year warranty.



ENCOOL

ENDUREPEL™
ARMOUR

*This term and any corresponding data refer to typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions. This information is offered for your general guidance only. It's accurate to the best of our knowledge and is not intended to relieve the user from their responsibility to investigate and understand other pertinent sources of information and to comply with all laws and procedures applicable to the safe handling and use of this material. Final determination of the suitability of any product for an application rests with the user.

Stance



ENNIS
FABRICS

CANADA ENGLISH 800 663 6647 • FRANÇAIS 888 663 6647
USA 877 953 6647
FAX 888 274 2910
ORDERS@ENNISFABRICS.COM
ENNISFABRICS.COM